

PRIMA. TECHNICAL CHARACTERISTICS

PRIMA

CONTROL PANEL		
ALTERNATIVES	Soft Touch Keyboard (AC PLUS)	✓
	Touch screen 7" (AC TOUCH)	✓
	Touch screen 9,7" with PLC and inverter (AIRTHERM)	-
BOOTH		
	White Pre-painted modular panels dimension 500 mm	-
	40 mm thick walls with polyurethane insulation	✓
	60 mm thick walls with mineral wool insulation	-
	Doors with large glasses	✓
	Pre-painted galvanized corrosion proof panels	✓
	Vertical corner lights	○
	Inclined ceiling lights	✓
	Horizontal side wall lights	-
	Vertical side/rear wall lights	○
	Partial filtration filtering plenum	✓
	Total filtration filtering plenum	-
	Easy service ceiling filter frames	✓
	Metal base floor (in alternative to pit floor)	○
	Downdraft air flow	✓
	Semi-downdraft air flow	○
	Service door	○
	CNC machined aluminum hinges	-
	Machined aluminum door handle	-
	Integrated control panel in door pillar	-
HEATING SYSTEMS		
ALTERNATIVES	Gas direct flame	✓
	Stainless steel combustion chamber with 4 flues revolutions	✓
	Hot water or steam heat exchanger	○
	Electric heating battery	○
	Cross flow or rotative heat recovery unit	○

✓ STANDARD ○ OPTIONAL - NOT AVAILABLE

Polin-AC srl

Viale della Tecnica, 2 | 37064 Povegliano Veronese (VR) | tel. +39 045 860 0992

info@polin-ac.it | www.polin-ac.it